



SlimPAR Pro Q USB

SlimPAR Pro Q USB is a high-powered quad-color (RGBA), low-profile washlight with D-Fi USB compatibility for wireless control. Dynamic and natural-looking amber LEDs provide expanded color mixing capabilities. Added light spill control is possible because the fixture is compatible with most 7.5" barn doors. Easily control static colors and automated programs with the optional [JRC-6](#) remote and increase standalone versatility with multiple user-configurable settings. Fits best in the [CHS-30 VIP Gear Bag](#).



Highlights

- LED Par designed for any application in need of a high-power quad-color (RGBA), low-profile wash light
- D-Fi USB compatibility for wireless Master/Slave or DMX control
- Compatible with most 7.5" Barndoors for added light control
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with punchy amber LEDs
- Flicker-free operation suitable for on-camera use
- Easily control static colors and automated programs with the optional IRC-6 remote
- Ideal for quiet applications due to silent operation and no moving parts
- Increase standalone versatility with multiple user-configurable settings
- Save time running cables and extension cords by power linking multiple units
- Fits best in the CHS-30 VIP Gear Bag
- Compact design easily fits inside sticks of TRUSST®

Specifications

- DMX Channels: 4, 5 or 10
- DMX Connectors: 3-pin XLR
- Light Source: 12 (quad-color RGBA) 6 W (2 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 31 Hz
- Beam Angle: 16°
- Field Angle: 31°
- Illuminance: 5,690 lux @ 2 m, 1,015 lux @ 5 m
- Power Linking: 7 units @ 120 V; 13 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 82 W, 1 A @ 120 V, 60 Hz 78 W, 0.6 A @ 230 V, 50 Hz
- Weight: 7.2 lb (3.3 kg)
- Size: 10 x 3.9 x 11.4 in (253 x 98 x 290 mm)
- Approvals: CE, MET
- Optional Controllers: IRC-6, D-Fi USB

What's Included

- Power cord
- Gel Frame
- Gel Frame Holder
- Warranty card
- Quick Reference Guide